

Ceramic Industrial Flat Fan Spray Nozzles



CC

Performance Data

Spray angle at 3 bar	Flow code	VEEJET nozzle Nozzle type/inlet connector										Equivalent orifice dia.	Flow (L/min)											Spray angle														
		H-VV		H-VVL		H-U				U			0.3bar	1bar	2bar	3bar	4bar	5bar	6bar	7bar	10bar	20bar	35bar	1.5bar	3bar	6bar	14bar											
		1/8	1/4	1/8	1/4	1/8	1/4	3/8	1/2	3/4	1 1/4		2																									
65°	6504	●	●	●	●																																	
	6505	●	●	●	●																																	
	6506	●	●	●	●																																	
	6508	●	●	●	●																																	
	6510					●	●	●																														
	6515					●	●	●	●																													
	6520					●	●		●																													
	6530					●	●																															
	6540					●	●	●																														
	6550					●	●	●	●																													

Ceramic Industrial Flat Fan Spray Nozzles have the following features:

- 303,304 Or 316SS materials of nozzle body with ceramic inserted spray tip
- Ceramic is fixed firmly in the nozzle body which can bear high pressure impact
- Ceramic Industrial Flat Fan Spray Nozzles produce a linear spray.
- Spray angle is usually 65°
- General Application :

Cleaning

Rinsing

Washing

Car Washing