

Quick Jet Flat Fan Quick Dismantling Nozzle



QC



Flat fan pattern

Style No.(spray angle at 3bar)					Flowrate(Liters/minute)								
50°	65°	80°	95°	110°	0.3bar	1bar	2bar	3bar	4bar	5bar	6bar	7bar	14bar
					0.12	0.23	0.32	0.39	0.46	0.51	0.56	0.60	0.85
	QC6502	QC8002			0.25	0.45	0.64	0.79	0.91	1.0	1.1	1.2	1.7
			QC69503		0.37	0.69	0.97	1.2	1.4	1.5	1.7	1.8	2.6
					0.50	0.92	1.3	1.6	1.8	2.0	2.2	2.4	3.4
	QC6505	QC8005	QC9505		0.62	1.1	1.6	2.0	2.3	2.5	2.8	3.0	4.3
	QC6506	QC8006			0.75	1.3	1.9	2.4	2.7	3.1	3.3	3.6	5.1
	QC6508	QC8008	QC9508		1.0	1.8	2.6	3.2	3.6	4.1	4.5	4.8	6.8
	QC6510	QC8010	QC9510		1.2	2.3	3.2	3.9	4.6	5.1	5.6	6.0	8.5
	QC6515				1.9	3.4	4.8	5.9	6.8	7.6	8.4	9.0	12.8
		QC8020			2.5	4.6	6.5	7.9	9.1	10.2	11.2	12.1	17.1
	QC6530				3.7	6.8	9.7	11.8	13.7	15.3	16.7	18.1	26

Quick jet flat fan quick dismantling nozzle has the following features:

- Quick jet flat fan quick dismantling nozzle requires a quick 1/4' ' and 3/8' ' turn of the wrist to remove spray tips. No tools are required.
- Choose with angles from 65° to 95°. Material is an engineering grade of polypropylene
- Quick jet flat fan quick dismantling nozzle features a retainer cap. Simply unscrew the cap and remove the spray tip. Insert the new tip and tighten the retainer cap.
- General Application :

Industrial plating

Etching machine

Development

PCB washing or cleaning

Cooling

Metal finishing

Coating