

Split-eyelet Nozzle Connector Adapter Fittings



Split-eyelet Nozzle Connector Adapter Fittings has the following features:

- Split-eyelet Nozzle Connector Adapter Fittings provide fast and economical way to install nozzles, gauges, hoses and other fittings in piping systems.
- Split-eyelet Nozzle Connector Adapter Fittings Eliminates cutting, threading, brazing.
- Split-eyelet Nozzle Connector Adapter Fittings bodies machined from bar stock brass or stainless steel with a choice of outlet connection sizes.
- Split-eyelet Nozzle Connector Adapter Fittings does not need any body rotation within the flange when installing or removing nozzles.
- Reduced sediment and minimal clogging as inlet extends into the pipe.
- 303SS, 304SS, 316SS materials are available



7521

Pressure: 17bar
Flow rate: 11L/min
Outlet connector:
1/8" or 1/4" NPT or
BSPT(female)



8370

Pressure: 9bar
Flow rate: 45L/min
Outlet connector:
1/4" or 3/8" NPT or
BSPT(female)



15475

Pressure: 9bar
Flow rate: 136L/min
Outlet connector:
1/2", 3/4", 1" NPT or
BSPT(female)



12521

Pressure: 70bar
Flow rate: 19L/min
Outlet connector:
1/8", 1/4" NPT or
BSPT(female)

Performance Data

Split hole connector No.	Pipe		Outlet connector NPT 或 BSPT				Common material			Max Pressure Bar	Max Flow L/min		
	Pipe size /Inch	Pipe outer Dia (mm)					A*	B*	C*				
7521	1/2	20-22	1/8	1/4				●	●	●			
	3/4	25-27	1/8	1/4				●	●	●	17	11	
	1	32-35	1/8	1/4				●	●	●			
12521	1/2	20-22	1/8	1/4				●	●	●			
	3/4	25-27	1/8	1/4				●	●	●	70	19	
	1	32-35	1/8	1/4				●	●	●			
8370	1-1/4	39-43		1/4	3/8	1/2		●	●	●			
	1-1/2	44-53		1/4	3/8	1/2		●	●	●	9	45	
	2	54-60		1/4	3/8	1/2		●	●	●			
15475	2-1/2	63-73				1/2	3/4	1	●	●	●		
	3	76-89				1/2	3/4	1	●	●	●	9	136
	4	102-114				1/2	3/4	1	●	●	●		